

abc command-line options

October 22, 2004

Contents

1	General Options	2
2	Input Options	2
3	Output Options	2
4	Warning/Error Reporting Options	2
5	Language Options	2
6	Optimization Options	2

1 General Options

- h , -help Prints the usage screen for abc.
- v , -version Print the abc version number. The underlying versions of soot and polyglot, which form part of abc, are also printed.
- verbose Display information about what abc is doing as it runs.
- @*(filename)*, -argfile *(filename)* Read a list of arguments from the file *filename* and behave as if they had been passed directly on the command-line.

2 Input Options

- sourceroots *(path)* Compile all .java files found in the directories given by *path* and any of their sub-directories.
- injars *(jar list)* Use all the class files in the jar files specified by *jar list* as source.
- inpath *(dir list)* Use all the class files in the directories specified by *dir list* as source.
- cp *(classpath)*, -classpath *(classpath)* Specify a list of zips, jars and directories that will be used when searching for libraries referred to in the code being compiled. The default value is the classpath abc is invoked with.

3 Output Options

- dava (default value: false) After weaving, run the Dava decompiler to produce Java source files of the woven code rather than outputting class files.
- outjar *(jar)* Write output class files into the jar file specified by *jar*.
- d *(path)* Write output class files into the directory specified by *path*.

4 Warning/Error Reporting Options

- warn-unused-advice (default value: true) If a piece of advice does not apply at any join point shadow, generate a warning.

5 Language Options

- nested-comments If this option is enabled, comments of the form `/* ... /* ... */ ... */` will be allowed.
- ext *(package name)* Load the AspectJ language extension defined in the package given by *package name*. For example, abc.eaj specifies the EAJ language extension supplied with abc.
- 1.3 Switch to Java 1.3 compliance mode. The default is 1.4.
- 1.4 Use Java 1.4 compliance mode. This is the default.

6 Optimization Options

- O*arg* (default value: 1) Set the general optimization level. 0 means no optimizations, and 1 means the standard intra-procedural options.